



1. Please use the grease specified by our company
2. The * in the drawing is the installation reference size, please follow the installation size requirements.
3. If the product performance parameters are not specified, please refer to the latest catalog of our company for the standard values.

Laifual

FSG-17-XX-C-I				Model	Reduction ratio	Rated torque at 2000r/min input		Permissible peak torque at start and stop		Permissible maximum value for average load torque		Permissible maximum momentary torque		Permissible maximum input rotational speed		Permissible average input rotational speed		Backlash	weight	Desian life
MODEL	U	T	W			Nm	kgfm	Nm	kgfm	Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min	r/min			
Wave generator-A Ø8	Ø8H7	9.4 ^{±1}	3JS9/P9	17	50	21	2.1	44	4.5	34	3.4	91	0	7300	3500	≤20	FSG-C:0.15	≥10000		
					80	29	2.9	56	5.7	35	3.6	113	12	7300	3500	≤20		≥15000		
Wave generator-A Ø11	Ø11H7	12.8 ^{±1}	4JS9/P9		100	31	3.2	70	7.2	51	5.2	143	15	7300	3500	≤20		≥15000		
					120	31	3.2	70	7.2	51	5.2	12	11	7300	3500	≤20		≥15000		