



Laitua!

FSG-40-XX-U-I																			
MODEL		U	T	W															
Wave generator-A φ14	φ14H7	16.3 ^{+0.1}	5JS9/P9																
Wave generator-A φ19	φ19H7	21.8 ^{+0.1}	6JS9/P9																
		80	268	27	675	69	369	38	1270	130	4000	3500	≤20						
		100	345	35	738	75	484	49	1400	143	4000	3500	≤20	FSG-14.6					
		120	382	39	802	82	586	60	1510	154	4000	3500	≤20	≥15000					
		160	382	39	814	86	586	60	1510	154	4000	3500	≤20	≥15000					
Wave generator-A φ22	φ22H7	24.8 ^{+0.1}	6JS9/P9																
		25.3 ^{+0.1}	8JS9/P9																
Model				Reduction ratio	Rated torque at2000r/min Input		Permissible peak torque at start and stop		Permissible maximum value for average load torque		Permissible maximum momentary torque		Permissible maximum input rotational speed		Permissible average input rotational speed		Backlash	weight	Desian life
Nm	kgfm	Nm	kgfm		Nm	kgfm	Nm	kgfm	r/min	r/min	Arc Sec	kg	Hour						
				50	178	18	523	53	255	26	892	91	4000	3500	≤20	≥10000			
				80	268	27	675	69	369	38	1270	130	4000	3500	≤20	≥15000			
				100	345	35	738	75	484	49	1400	143	4000	3500	≤20	≥15000			
				120	382	39	802	82	586	60	1510	154	4000	3500	≤20	≥15000			
				160	382	39	814	86	586	60	1510	154	4000	3500	≤20	≥15000			