





Technical requirements:

1. Please use the grease specified by our company
2. The * in the drawing is the installation reference size, please follow the installation size requirements.
3. If the product performance parameters are not specified, please refer to the latest catalog of our company for the standard values.

D Direction



Laifual

FSS-17-XX-U-I-LF				Model		Reduction ratio	Rated torque at 2000r/min input		Permissible peak torque at start and stop		Permissible maximum value for average load torque		Permissible maximum momentary torque		Permissible maximum input rotational speed		Permissible average input rotational speed		Backlash	weight	Design life
MODEL	U	T	W	Model			Nm	kgfm	Nm	kgfm	Nm	kgfm	Nm	kgfm	r/min		r/min		Arc Sec	kg	Hour
Wave generator-A φ8	φ8H7	9.4 ^{±0.1}	3JS9/P9	17		50	16	1.6	34	3.5	26	2.6	70	7.1	7300		3500		≤20		≥10000
						80	22	2.2	43	4.4	27	2.7	87	8.9	7300		3500		≤20	FSS-I:0.67	≥15000
						100	24	2.4	54	5.5	39	4	108	11	7300		3500		≤20		≥15000
Wave generator-A φ11	φ11H7	12.8 ^{±0.1}	4JS9/P9			120	24	2.4	54	5.5	39	4	86	8.8	7300		3500		≤20		≥15000